

**Diametri Tubi senza saldatura alta pressione
Size seamless HP Tube**

Nominal Thickness			Rating Service		Outside Diameter Tolerance				Inside Diameter Tolerance				
Inch	mm	mm	PSI	BAR	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm
1/4"	6,35	2,09	60000	4136	6,35	0,248	6,299	0,243	6,172	0,079	2,007	0,083	2,108
1/4"	6,35	1,77	20000	1378	6,35	0,248	6,299	0,243	6,172	0,079	2,007	0,083	2,108
5/16"	7,93	3,14	150000	10342	7,93	0,310	7,874	0,306	7,772	0,059	1,499	0,063	1,600
3/8"	9,53	3,11	60000	4136	9,53	0,37	9,398	0,365	9,271	0,121	3,073	0,125	3,175
3/8"	9,53	2,12	20000	1378	9,53	0,37	9,398	0,365	9,271	0,198	5,029	0,203	5,156
9/16"	14,28	4,70	60000	4136	14,28	0,557	14,148	0,552	14,021	0,182	4,623	0,187	4,750
9/16"	14,28	3,90	40000	2757	14,28	0,557	14,148	0,552	14,021	0,245	6,223	0,25	6,350
9/16"	14,28	3,11	20000	1378	14,28	0,557	14,148	0,552	14,021	0,307	7,798	0,312	7,925
9/16"	14,28	2,67	10000	689	14,28	0,557	14,148	0,552	14,021	0,354	8,992	0,359	9,119
3/4"	19,05	6,29	60000	4136	19,05	0,745	18,923	0,740	18,796	0,245	6,223	0,250	6,350
3/4"	19,05	3,91	20000	1378	19,05	0,745	18,923	0,740	18,796	0,432	10,973	0,437	11,100
3/4"	19,05	2,92	10000	689	19,05	0,745	18,923	0,740	18,796	0,51	12,954	0,515	13,081
1"	25,40	7,08	30000	2068	25,40	0,995	25,273	0,990	25,146	0,432	10,973	0,438	11,125
1"	25,40	5,50	20000	1378	25,40	0,955	25,273	0,990	25,146	0,557	14,148	0,562	14,275
1"	25,40	3,91	10000	689	25,40	0,955	25,273	0,990	25,146	0,682	17,323	0,687	17,450

Quality: TP 304/304L - TP 316/316L - UNS 31803 - UNS 32750-32760 - INC 625 - UNS 31254

